

What is claimed is:

1. A surface acoustic wave device comprising:  
a piezoelectric substrate having a pair of substrate edges and an upper surface therebetween and including a main region and a bottom surface, the piezoelectric substrate having at least one inner edge arranged to contact the main region and to extend from the upper surface toward the bottom surface of the piezoelectric substrate inside one of the substrate edges;

an interdigital transducer provided on the main region of the piezoelectric substrate such that a shear horizontal type surface acoustic wave excited by the interdigital transducer and having a wavelength of  $\lambda$  are reflected by the at least one inner edge;

wherein a distance L between the at least one inner edge and the corresponding one of the substrate edges is substantially equal to about  $8\lambda$  or less.

2. A surface acoustic wave device according to claim 1, wherein the at least one inner edge has a height H in the range of about  $2\lambda$  to about  $6\lambda$ .

3. A surface acoustic wave device according to claim 1, wherein the surface acoustic wave device comprises one of a surface acoustic wave resonator, a longitudinally coupled resonator filter, a transversely coupled resonator filter, and a ladder type filter.

4. A surface acoustic wave device according to claim 1, wherein the piezoelectric substrate is made of at least one of piezoelectric ceramics and piezoelectric single crystals.

SUB  
B2

5. A surface acoustic wave device according to claim 1, wherein the upper surface of the piezoelectric substrate has a pair of grooves arranged substantially parallel to the substrate edges and extending from the upper surface toward the bottom surface.

6. A surface acoustic wave device according to claim 5, wherein the pair of grooves have inside surfaces arranged to contact the main region of the upper surface and defining inner edges for the main region.

7. A surface acoustic wave device according to claim 1, wherein the inside surfaces define reflection edges for reflecting the shear horizontal type surface acoustic wave.

8. A surface acoustic wave device according to claim 5, wherein at least two IDTs are disposed between the grooves on the upper surface of the piezoelectric substrate.

Sub 7  
C3

9. A surface acoustic wave device according to claim 8, wherein the at least two IDTs include a plurality of electrode fingers, and if the wavelength of the surface acoustic wave is represented by  $\lambda$ , the widths of the outermost electrode fingers of the at least two IDTs are approximately  $\lambda/8$  and the widths of all of the other electrode fingers are approximately  $\lambda/4$ .

10. A communication device comprising:  
at least one surface acoustic wave device including:  
a piezoelectric substrate having a pair of substrate edges and an upper surface therebetween and



sub  
B4  
cmcd

of the upper  
region.

۱۷۷

device ac  
d between  
tric subst

من علی

[illegible]